



## Dual Temperature Alarm

- Standalone or integration with alarm panel
- Audible alarm can be easily silenced
- Desktop or wall mount installation
- High/low temp alarms with separate outputs

## OVERVIEW

This dual temperature alarm is designed to protect food or valuable assets from spoilage or damage caused by temperature falling outside of safe ranges.

## FEATURES

- Simultaneous operation of local and remote sensors
- Standalone or integration with alarm panel
- Easy to set and adjust low and high temperature limit
- Separate alarm outputs for low and high temperature
- Two line LED display to show local and remote temperature
- Audible alarm can be easily silenced
- Desktop or wall mount installation for the local unit
- Wall mounting faceplate included for remote sensor
- Suits almost any industry or environment where consistent temperature is a concern

\*Electronic Security Sales (ESS) warrants its hardware products to you to be free from defects in materials and assembly in the course of normal use and service from the date of shipment by ESS to you or the period of time specified on ESS documentation.

## SPECIFICATIONS

**Product Code**  
E50014

**Dimensions**  
W: 130mm x L: 90mm x H: 35mm

**Accuracy**  
± 1.8°C

**Local Operating Temperature**  
0°C to 60°C

**Power Supply**  
DC: 9 - 15V

**Standby Current**  
≤35mA

**Operational Current**  
≤300mA

**Remote Sensor Operating Temperature**  
-40°C to 60°C

**Audible Alarm**  
0 to 90dB/m, adjustable

**Warranty**  
1 Year\*