

GTU1

Integrated Mount Tester

- 4" IPS screen and Qwerty flip keyboard with 45 keys
- IP configuration via Onvif Protocol
- HDCVI/Analog Self-adaptive access
- 8x Digital Zoom
- Audio & RS485 control
- TDR cable detection & network connection test
- Video screenshot, video recording and playback
- Supports PoE & 12V power supply
- Dual LED flashlight



TECHNICAL SPECIFICATIONS

PHYSICAL PORT

Ethernet Port 2x 10/100/1000M RJ45 port
 Function Port 2x BNC port (Video IN / OUT)
 1x RS485, 1x Audio IN, 1x USB

IPC TEST

Protocol ONVIF 2.4.1, RTSP, RTP
 Ethernet Test 10/100/1000M Ethernet link test, loop detect, ethernet traffic, link quality test
 IP Configuration Static IP, DHCP Client, DHCP Server
 IPC Test Discover camera, real time video, camera configuration, PTZ control, audio test, full screen preview and 8x digital zoom, snapshot, record video.

HDCVI & ANALOG TEST

Format NTSC, PAL
 Resolution D1, 720P, 1080P
 Signal Level 1Vpp
 Camera Test Real time video, PTZ control, audio test, full screen preview, 8x digital zoom, snapshot, record video.
 HDCVI OSD Camera configuration

PTZ CONTROL

Protocol More than 30 protocols
 Baud Rate 150, 300, 600, 1200, 2400, 4800, 9600, 19200bps

DETECTION

TDR detection 0~150m net cable detection
 PoE Test PD test, PSE test
 Network Analyse Sniff, list subnet, ping
 Analog Video Generator Generate PAL/NTSC video signal
 Record Playback Support local playback

SYSTEM SPECIFICATION

Screen 4.0" TFT (800x480 WVGA), Backlight Brightness Adjustable
 Operation Method Power Key, 12 Control Keys, Qwerty Keyboard with 45 keys
 Auto Power Off Disable / 5~60 minutes
 Keyboard Tone Enable / Disable
 Upgrade Support online upgrade

OTHER

Power Input PoE port by PoE midspan
 PoE Midspan Input AC100~230V 50~60Hz, Output 48V/15w
 Battery Dedicate battery, user replaceable, 7.4V lithium-ion, 22.2Wh
 Power Output PoE (802.3af, 802.3at), DC12V 2A
 Time Charging time 3~4 hours
 Internal Storage 8GB flash
 LED Light 2x 35lm LED light
 Working Temperature -10°C ~ +55°C
 Working Humidity 30% ~ 90%
 Dimensions 190 x 113 x 37mm
 Weight 0.5kg

ORDERING INFORMATION

Model #	Order #	Description
GTU1	E49519	galileo Integrated Mount Tester

EXCLUSIVELY DISTRIBUTED BY

ELECTRONIC SECURITY SALES

PHONE: 1300 377 379

EMAIL: orders@esecuritysales.com

www.eSecuritySales.com/galileo