

# PS1008D

## 8 Port Ethernet PoE Switch

- Layer 2 commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3x
- MAC auto learning, aging
- Supports MDI/MDIX self-adaption
- RJ45 ports support 10/100/1000Mbps self-adaptation
- Supports IEEE802.3af, IEEE803.3at power standards
- Metal enclosure
- Supports 1 port Hi-PoE 60W
- Supports DC48-57V power supply



### TECHNICAL SPECIFICATIONS

Ethernet Port	8 x 10/100Mbps PoE ports 2 x 10/100/1000Mbps ports
PoE Power Consumption	Port 1: ≤60W, Port 2-8: ≤30W Total: ≤96W
PoE Protocol	IEEE802.3af, IEEE803.3at, Hi-PoE
Switching Capacity	5.6Gbps
Packet Forwarding Rate	4.17Mbps
Packet Buffer Memory	4Mb
MAC Table Size	16k
Flow Control	Enable by default
Application Humidity	10% ~ 90%
Power	DC48~57V power adapter
Lighting Protection	Common Mode: 2KV Differential Mode: 0.5KV
Working Temperature	-10°C ~ +55°C
Weight	0.49kg
Dimension (WxDxH)	190mm x 100mm x 30mm

### ORDERING INFORMATION

Model #	Order #	Description
PS1008D	E31002	8 Port Ethernet PoE Switch

EXCLUSIVELY DISTRIBUTED BY

**ELECTRONIC SECURITY SALES**

**PHONE:** 1300 377 379

**EMAIL:** orders@esecuritysales.com

[www.eSecuritySales.com/galileo](http://www.eSecuritySales.com/galileo)